

Zero-Drift, Rail-to-Rail I/O CMOS Operational Amplifiers

Features

- Low Offset Voltage: 20 μ V (MAX)
- Input Offset Drift: 0.1 μ V/ $^{\circ}$ C(TYP)
- High Gain Bandwidth Product: 11MHz
- Rail-to-Rail Input and Output
- High Gain, CMRR, PSRR:120dB(TYP)
- High Slew Rate: 8.5V/ μ s
- Low Noise: 0.48 μ Vp-p (0.01~10Hz)
- Low Power Consumption: 1.3mA /op amp
- Overload Recovery Time: 0.4us
- Low Supply Voltage: +2.9 V to +5.5 V
- No External Capacitors Required
- Extended Temperature: -40 $^{\circ}$ C to +125 $^{\circ}$ C

Applications

- Temperature Sensors
- Medical/Industrial Instrumentation
- Pressure Sensors
- Battery-Powered Instrumentation
- Active Filtering
- Weight Scale Sensor
- Strain Gage Amplifiers
- Power Converter/Inverter

Description


The RS8561, RS8562, RS8564, RS8563(dual version & shutdown) series of CMOS operational amplifiers use auto-zero techniques to simultaneously provide very low offset voltage (20 μ V max) and near-zero drift over time and temperature. This family of amplifiers has ultralow noise, offset and power.

This miniature, high-precision operational amplifiers offset high input impedance and rail-to-rail input and rail-to-rail output swing. With high gain-bandwidth product of 11MHz and slew rate of 8.5V/ μ s.

Single or dual supplies as low as +2.9V (\pm 1.45V) and up to +5.5V (\pm 2.75V) may be used.

The RS8561/RS8562/RS8564/RS8563 (dual version with shutdown) are specified for the extended industrial and automotive temperature range (-40 $^{\circ}$ C to 125 $^{\circ}$ C). The RS8561 single amplifier is available in 5-lead SOT23, 8-lead MSOP8 and 8-lead SOIC packages, The RS8562 dual amplifier is available in 8-lead SOIC and 8-lead MSOP narrow surface mount packages, The RS8563(dual version with shutdown) comes in Micro-SIZE MSOP-10. The RS8564 quad is available in 14-lead SOIC and 14-lead narrow TSSOP packages.

PIN CONFIGURATIONS



ABSOLUTE MAXIMUM RATINGS⁽¹⁾

Supply Voltage, V+ to V-.....	7.0V
Input Terminals, Voltage ⁽²⁾	- 0.5 to (V+) + 0.5V
Current ⁽²⁾	±10mA
Storage Temperature	-65°C to +150°C
Operating Temperature	-40°C to +125°C
Junction Temperature.....	150°C
Package Thermal Resistance @ TA = +25°C	
SOT23-5, SOT23-6.....	200°C/W
MSOP-10, SOIC-8	150°C/W
SOIC-14, TSSOP-14.....	100°C/W
Lead Temperature (Soldering, 10s)	260°C
ESD Susceptibility	
HBM	5000V
MM	400V



ESD SENSITIVITY CAUTION

ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because very small parametric changes could cause the device not to meet its published specifications.

(1) Stresses above these ratings may cause permanent damage. Exposure to absolute maximum conditions for extended periods may degrade device reliability. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those specified is not implied.

(2) Input terminals are diode-clamped to the power-supply rails. Input signals that can swing more than 0.5V beyond the supply rails should be current-limited to 10mA or less.

PACKAGE/ORDERING INFORMATION

PRODUCT	ORDERING NUMBER	TEMPRANGE	PACKAGE	PACKAGE MARKING	TRANSPORT MEDIA,QUANTITY
RS8561	RS8561XF	-40°C ~125°C	SOT23-5	8561	Reel,3000
	RS8561XK	-40°C ~125°C	SOIC-8(SOP8)	RS8561	Reel,2500
	RS8561XM	-40°C ~125°C	MSOP-8	RS8561	Reel,3000
RS8562	RS8562XK	-40°C ~125°C	SOIC-8(SOP8)	RS8562	Reel,2500
	RS8562XM	-40°C ~125°C	MSOP-8	RS8562	Reel,3000
RS8563	RS8563XN	-40°C ~125°C	MSOP-10	RS8563	Reel,3000
RS8564	RS8564XP	-40°C ~125°C	SOIC-14(SOP14)	RS8564	Reel,2500
	RS8564XQ	-40°C ~125°C	TSSOP-14	RS8564	Reel,3000

ELECTRICAL CHARACTERISTICS







Boldface limits apply over the specified temperature range, $T_A = -40^\circ\text{C}$ to $+125^\circ\text{C}$.

(At $T_A = +25^\circ\text{C}$, $V_s = 5\text{V}$, $R_L = 10\text{k}\Omega$ connected to $V_s/2$, and $V_{\text{OUT}} = V_s/2$, unless otherwise noted.)

PARAMETER	CONDITION	RS8561, RS8562, RS8563, RS8564			UNIT
		MIN	TYP	MAX	
OFFSET VOLTAGE					
Input Offset Voltage	V_{os}		± 3	± 20	μV
VS Temperature	dV_{os}/dT		0.1	0.4	$\mu\text{V}/^\circ\text{C}$
VS Power Supply	PSRR	$V_s = +2.9\text{V}$ to $+5.5\text{V}$, $V_{\text{CM}} = 0$	100	120	dB
Channel Separation, dc			0.1		$\mu\text{V/V}$
INPUT BIAS CURRENT					
Input Bias Current	I_B	$V_{\text{CM}} = V_s/2$	100		pA
Input Offset Current	I_{os}		10		pA
NOISE PERFORMANCE					
Input Voltage Noise	e_{npp}	$f=0.01\text{Hz}$ to 10Hz		0.48	μVpp
Input Voltage Noise	e_{npp}	$f=0.01\text{Hz}$ to 1Hz		0.15	μVpp
Input Voltage Noise Density	e_n	$f=1\text{KHz}$		32	$\text{nV}/\sqrt{\text{Hz}}$
Input Current Noise Density	i_n	$f=10\text{Hz}$		1.5	$\text{fA}/\sqrt{\text{Hz}}$
INPUT VOLTAGE RANGE					
Common-Mode Voltage Range	V_{CM}		$(V-) - 0.1\text{V} < V_{\text{CM}} < (V+) + 0.1\text{V}$	$(V-) - 0.1$	V
Common-Mode Rejection Ratio	CMRR		100	120	dB
INPUT CAPACITANCE					
Differential				5	pF
Common-Mode				5	pF
OPEN-LOOP GAIN					
Open-Loop Voltage Gain	A_{OL}	$RL=10\text{k}\Omega$, $VO=0.3\text{V}$ to 4.7V , -40°C ~ 125°C	100	120	dB
DYNAMIC PERFORMANCE					
Slew Rate	SR	$G=+1$		8.5	$\text{V}/\mu\text{s}$
Gain-Bandwidth Product	GBW			11	MHz
Overload Recovery Time				0.4	us
OUTPUT CHARACTERISTICS					
Output Voltage High	V_{OH}	$RL=100\text{ K}\Omega$ to GND	4.99	4.998	V
		$RL=10\text{ K}\Omega$ to GND	4.95	4.98	V
Output Voltage Low	V_{OL}	$RL=100\text{ K}\Omega$ to V_+		1	mV
		$RL=10\text{ K}\Omega$ to V_+		10	mV
Short-Circuit Current	I_{SC}			65	mA
POWER SUPPLY					
Operating Voltage Range			2.9	5.5	V
Quiescent Current/ Amplifier	I_Q		1.3	1.55	mA
SHUTDOWN					
t_{OFF}				2	μs
t_{ON}				150	us
V_L (shutdown)			0	+0.8	V
V_H (amplifier is active)			0.75(V_+)	V_+	V
Input Bias Current of Enable Pin				50	pA
I_{QSD}				1	uA







TYPICAL CHARACTERISTICS

At $T_A = +25^\circ\text{C}$, $V_s=5\text{V}$, $R_L = 10\text{k}\Omega$ connected to $V_s/2$, $V_{\text{OUT}} = V_s/2$, unless otherwise noted.



TYPICAL CHARACTERISTICS


At $T_A = +25^\circ\text{C}$, $V_s=5\text{V}$, $R_L = 10\text{k}\Omega$ connected to $V_s/2$, $V_{\text{OUT}} = V_s/2$, unless otherwise noted.




TYPICAL CHARACTERISTICS

At $T_A = +25^\circ\text{C}$, $V_s=5\text{V}$, $R_L = 10\text{k}\Omega$ connected to $V_s/2$, $V_{\text{OUT}} = V_s/2$, unless otherwise noted.


POSITIVE OVERTIME RECOVERY




NEGATIVE OVERTIME RECOVERY




0.01Hz TO 10Hz NOISE AT $V_s=5\text{V}$




0.01Hz TO 10Hz NOISE AT $V_s=2.9\text{V}$



0.01Hz TO 1Hz NOISE AT $V_s=5\text{V}$



0.01Hz TO 1Hz NOISE AT $V_s=2.9\text{V}$



APPLICATION NOTES

The RS8561, RS8562, RS8563, RS8564 series op amps are unity-gain stable and free from unexpected output phase reversal. They use auto-zeroing techniques to provide low offset voltage and very low drift over time and temperature.

Good layout practice mandates use of a $0.1\mu\text{F}$ capacitor placed closely across the supply pins.

For lowest offset voltage and precision performance, circuit layout and mechanical conditions should be optimized. Avoid temperature gradients that create thermoelectric (Seebeck) effects in thermocouple junctions formed from connecting dissimilar conductors. These thermally-generated potentials can be made to cancel by assuring that they are equal on both input terminals.

- Use low thermoelectric-coefficient connections (avoid dissimilar metals).
- Thermally isolate components from power supplies or other heat-sources.
- Shield op amp and input circuitry from air currents, such as cooling fans.

Following these guidelines will reduce the likelihood of junctions being at different temperatures, which can cause thermoelectric voltages of $0.1\mu\text{V}/^\circ\text{C}$ or higher, depending on materials used.

OPERATING VOLTAGE

The RS8561, RS8562, RS8563, RS8564 series op amps operate over a power-supply range of $+2.9\text{V}$ to $+5.5\text{V}$ ($\pm 1.45\text{V}$ to $\pm 2.75\text{V}$). Supply voltages higher than 7V (absolute maximum) can permanently damage the amplifier. Parameters that vary over supply voltage or temperature are shown in the Typical Characteristics section of this data sheet.

RS8563 ENABLE FUNCTION

The enable/shutdown digital input is referenced to the $V-$ supply voltage of the amp. A logic high enables the op amp. A valid logic high is defined as >

75% of the total supply voltage. The valid logic high signal can be up to 5.5V above the negative supply, independent of the positive supply voltage. A valid logic low is defined as < 0.8V above the $V-$ supply pin. If dual or split power supplies are used, be sure that logic input signals are properly referred to the negative supply voltage. The Enable pin must be connected to a valid high or low voltage, or driven, not left open circuit.

The logic input is a high-impedance CMOS input, with separate logic inputs provided on the dual version. For battery operated applications, this feature can be used to greatly reduce the average current and extend battery life.

The enable time includes one full autozero cycle required by the amplifier to return to V_{os} accuracy. Prior to this time, the amplifier functions properly, but with unspecified offset voltage.

Disable time is $1\mu\text{s}$. When disabled, the output assumes a high-impedance state. This allows the RS8563 to be operated as a gated amplifier, or to have the output multiplexed onto a common analog output bus.

AYOUT GUIDELINES

Attention to good layout practices is always recommended. Keep traces short. When possible, use a PCB ground plane with surface-mount components placed as close to the device pins as possible. Place a $0.1\mu\text{F}$ capacitor closely across the supply pins. These guidelines should be applied throughout the analog circuit to improve performance and provide benefits such as reducing the EMI (electromagnetic-interference) susceptibility.








Figure 1. The Layout of Guard Ring

PACKAGE OUTLINE DIMENSIONS **SOT23-5**







RECOMMENDED LAND PATTERN (Unit: mm)




Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.050	1.250	0.041	0.049
A1	0.000	0.100	0.000	0.004
A2	1.050	1.150	0.041	0.045
b	0.300	0.500	0.012	0.020
c	0.100	0.200	0.004	0.008
D	2.820	3.020	0.111	0.119
E	1.500	1.700	0.059	0.067
E1	2.650	2.950	0.104	0.116
e	0.950(BSC)		0.037(BSC)	
e1	1.800	2.000	0.071	0.079
L	0.300	0.600	0.012	0.024
θ	0°	8°	0°	8°

MSOP-8



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.820	1.100	0.032	0.043
A1	0.020	0.150	0.001	0.006
A2	0.750	0.950	0.030	0.037
b	0.250	0.380	0.010	0.015
c	0.090	0.230	0.004	0.009
D	2.900	3.100	0.114	0.122
e	0.650(BSC)		0.026(BSC)	
E	2.900	3.100	0.114	0.122
E1	4.750	5.050	0.187	0.199
L	0.400	0.800	0.016	0.031
θ	0°	6°	0°	6°

MSOP-10




RECOMMENDED LAND PATTERN (Unit: mm)




Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.820	1.100	0.032	0.043
A1	0.020	0.150	0.001	0.006
A2	0.750	0.950	0.030	0.037
b	0.180	0.280	0.007	0.011
c	0.090	0.230	0.004	0.009
D	2.900	3.100	0.114	0.122
e	0.50(BSC)		0.020(BSC)	
E	2.900	3.100	0.114	0.122
E1	4.750	5.050	0.187	0.199
L	0.400	0.800	0.016	0.031
θ	0°	6°	0°	6°

TSSOP-14







RECOMMENDED LAND PATTERN (Unit: mm)







Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A		1.200		0.047
A1	0.050	0.150	0.002	0.006
A2	0.800	1.050	0.031	0.041
b	0.190	0.300	0.007	0.012
c	0.090	0.200	0.004	0.008
D	4.860	5.100	0.191	0.201
E	4.300	4.500	0.169	0.177
E1	6.250	6.550	0.246	0.258
e	0.650(BSC)		0.026(BSC)	
L	0.500	0.700	0.020	0.028
H	0.25(TYP)		0.01(TYP)	
θ	1°	7°	1°	7°

SOIC-8(SOP8)



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.350	1.750	0.053	0.069
A1	0.100	0.250	0.004	0.010
A2	1.350	1.550	0.053	0.061
b	0.330	0.510	0.013	0.020
c	0.170	0.250	0.007	0.010
D	4.800	5.000	0.189	0.197
e	1.270(BSC)		0.050(BSC)	
E	5.800	6.200	0.228	0.244
E1	3.800	4.000	0.150	0.157
L	0.400	1.270	0.016	0.050
θ	0°	8°	0°	8°

SOIC-14(SOP14)



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.350	1.750	0.053	0.069
A1	0.100	0.250	0.004	0.010
A2	1.350	1.550	0.053	0.061
b	0.310	0.510	0.012	0.020
c	0.100	0.250	0.004	0.010
D	8.450	8.850	0.333	0.348
e	1.270(BSC)		0.050(BSC)	
E	5.800	6.200	0.228	0.244
E1	3.800	4.000	0.150	0.157
L	0.400	1.270	0.016	0.050
θ	0°	8°	0°	8°